item ea		\$7,863.00	\$8,334.00 #7BWS10	item 1 has 2 alternates \$9,690.00 #BGS-22-110 \$9,333.00 #PDI2024-T10 (8 wks)
	Stacker  2,000 Pound Capacity Straddle Stacker Lift Truck 24 Volt SEM (Separately Excited Motor)  24 Volt – SEM Transistor Control with Auto Deceleration System, Integrated Hoist Control, and Three User-Selectable Performance Modes  72"/110"/0" FFH (1828/2794 MM) Simplex Mast  31.5" (800mm) Wide Class 2 Carriage  Two Speed Lift/Lower Controls  48" High Load Backrest Extension  1.5" x 4" x 42" – Class 2 Hook Type Forks  9" x 4" Molded-On Rubber Drive Tires  4" x 2.8" Single Poly Load Wheels  Knock-Out Load Wheel Axles  Adjustable Outrigger Width: (37", 42", 49", ID) – 42" Standard From Factory  48" Long Load Length	\$7,863.00	\$8,334.00 #7BWS10	\$9,690.00 #BGS-22-110 \$9,333.00 #PDI2024-T10
	Stacker  2,000 Pound Capacity Straddle Stacker Lift Truck 24 Volt SEM (Separately Excited Motor)  24 Volt – SEM Transistor Control with Auto Deceleration System, Integrated Hoist Control, and Three User-Selectable Performance Modes  72"/110"/0" FFH (1828/2794 MM) Simplex Mast  31.5" (800mm) Wide Class 2 Carriage  Two Speed Lift/Lower Controls  48" High Load Backrest Extension  1.5" x 4" x 42" – Class 2 Hook Type Forks  9" x 4" Molded-On Rubber Drive Tires  4" x 2.8" Single Poly Load Wheels  Knock-Out Load Wheel Axles  Adjustable Outrigger Width: (37", 42", 49", ID) – 42" Standard From Factory  48" Long Load Length	\$7,863.00	#7BWS10	#BGS-22-110 \$9,333.00 #PDI2024-T10
1 1	<ul> <li>2,000 Pound Capacity Straddle Stacker Lift Truck 24 Volt SEM (Separately Excited Motor)</li> <li>24 Volt – SEM Transistor Control with Auto Deceleration System, Integrated Hoist Control, and Three User-Selectable Performance Modes</li> <li>72"/110"/0" FFH (1828/2794 MM) Simplex Mast</li> <li>31.5" (800mm) Wide Class 2 Carriage</li> <li>Two Speed Lift/Lower Controls</li> <li>48" High Load Backrest Extension</li> <li>1.5" x 4" x 42" – Class 2 Hook Type Forks</li> <li>9" x 4" Molded-On Rubber Drive Tires</li> <li>4" x 2.8" Single Poly Load Wheels</li> <li>Knock-Out Load Wheel Axles</li> <li>Adjustable Outrigger Width: (37", 42", 49", ID) – 42" Standard From Factory</li> <li>48" Long Load Length</li> </ul>	\$7,863.00	#7BWS10	#BGS-22-110 \$9,333.00 #PDI2024-T10
	<ul> <li>24 Volt – SEM Transistor Control with Auto Deceleration System, Integrated Hoist Control, and Three User-Selectable Performance Modes</li> <li>72"/110"/0" FFH (1828/2794 MM) Simplex Mast</li> <li>31.5" (800mm) Wide Class 2 Carriage</li> <li>Two Speed Lift/Lower Controls</li> <li>48" High Load Backrest Extension</li> <li>1.5" x 4" x 42" – Class 2 Hook Type Forks</li> <li>9" x 4" Molded-On Rubber Drive Tires</li> <li>4" x 2.8" Single Poly Load Wheels</li> <li>Knock-Out Load Wheel Axles</li> <li>Adjustable Outrigger Width: (37", 42", 49", ID) – 42" Standard From Factory</li> <li>48" Long Load Length</li> </ul>			\$9,333.00 #PDI2024-T10
	and Three User-Selectable Performance Modes  72"/110"/0" FFH (1828/2794 MM) Simplex Mast  31.5" (800mm) Wide Class 2 Carriage  Two Speed Lift/Lower Controls  48" High Load Backrest Extension  1.5" x 4" x 42" – Class 2 Hook Type Forks  9" x 4" Molded-On Rubber Drive Tires  4" x 2.8" Single Poly Load Wheels  Knock-Out Load Wheel Axles  Adjustable Outrigger Width: (37", 42", 49", ID) – 42" Standard From Factory  48" Long Load Length			#PDI2024-T10
	<ul> <li>72"/110"/0" FFH (1828/2794 MM) Simplex Mast</li> <li>31.5" (800mm) Wide Class 2 Carriage</li> <li>Two Speed Lift/Lower Controls</li> <li>48" High Load Backrest Extension</li> <li>1.5" x 4" x 42" - Class 2 Hook Type Forks</li> <li>9" x 4" Molded-On Rubber Drive Tires</li> <li>4" x 2.8" Single Poly Load Wheels</li> <li>Knock-Out Load Wheel Axles</li> <li>Adjustable Outrigger Width: (37", 42", 49", ID) - 42" Standard From Factory</li> <li>48" Long Load Length</li> </ul>			#PDI2024-T10
	<ul> <li>31.5" (800mm) Wide Class 2 Carriage</li> <li>Two Speed Lift/Lower Controls</li> <li>48" High Load Backrest Extension</li> <li>1.5" x 4" x 42" - Class 2 Hook Type Forks</li> <li>9" x 4" Molded-On Rubber Drive Tires</li> <li>4" x 2.8" Single Poly Load Wheels</li> <li>Knock-Out Load Wheel Axles</li> <li>Adjustable Outrigger Width: (37", 42", 49", ID) - 42" Standard From Factory</li> <li>48" Long Load Length</li> </ul>			
	<ul> <li>31.5" (800mm) Wide Class 2 Carriage</li> <li>Two Speed Lift/Lower Controls</li> <li>48" High Load Backrest Extension</li> <li>1.5" x 4" x 42" - Class 2 Hook Type Forks</li> <li>9" x 4" Molded-On Rubber Drive Tires</li> <li>4" x 2.8" Single Poly Load Wheels</li> <li>Knock-Out Load Wheel Axles</li> <li>Adjustable Outrigger Width: (37", 42", 49", ID) - 42" Standard From Factory</li> <li>48" Long Load Length</li> </ul>			(8 wks)
	<ul> <li>Two Speed Lift/Lower Controls</li> <li>48" High Load Backrest Extension</li> <li>1.5" x 4" x 42" – Class 2 Hook Type Forks</li> <li>9" x 4" Molded-On Rubber Drive Tires</li> <li>4" x 2.8" Single Poly Load Wheels</li> <li>Knock-Out Load Wheel Axles</li> <li>Adjustable Outrigger Width: (37", 42", 49", ID) – 42" Standard From Factory</li> <li>48" Long Load Length</li> </ul>			
	<ul> <li>48" High Load Backrest Extension</li> <li>1.5" x 4" x 42" - Class 2 Hook Type Forks</li> <li>9" x 4" Molded-On Rubber Drive Tires</li> <li>4" x 2.8" Single Poly Load Wheels</li> <li>Knock-Out Load Wheel Axles</li> <li>Adjustable Outrigger Width: (37", 42", 49", ID) - 42" Standard From Factory</li> <li>48" Long Load Length</li> </ul>			
	<ul> <li>1.5" x 4" x 42" - Class 2 Hook Type Forks</li> <li>9" x 4" Molded-On Rubber Drive Tires</li> <li>4" x 2.8" Single Poly Load Wheels</li> <li>Knock-Out Load Wheel Axles</li> <li>Adjustable Outrigger Width: (37", 42", 49", ID) - 42" Standard From Factory</li> <li>48" Long Load Length</li> </ul>			
	<ul> <li>9" x 4" Molded-On Rubber Drive Tires</li> <li>4" x 2.8" Single Poly Load Wheels</li> <li>Knock-Out Load Wheel Axles</li> <li>Adjustable Outrigger Width: (37", 42", 49", ID) – 42" Standard From Factory</li> <li>48" Long Load Length</li> </ul>			
	<ul> <li>4" x 2.8" Single Poly Load Wheels</li> <li>Knock-Out Load Wheel Axles</li> <li>Adjustable Outrigger Width: (37", 42", 49", ID) – 42" Standard From Factory</li> <li>48" Long Load Length</li> </ul>			
	<ul> <li>Knock-Out Load Wheel Axles</li> <li>Adjustable Outrigger Width: (37", 42", 49", ID) – 42" Standard From Factory</li> <li>48" Long Load Length</li> </ul>			
	<ul> <li>Adjustable Outrigger Width: (37", 42", 49", ID) – 42" Standard From Factory</li> <li>48" Long Load Length</li> </ul>			İ
	· 48" Long Load Length			
	Impact Resistant, Ergonomically Designed Bottom Mounted Control Handle with Gas			
	Spring Return			
	Butterfly Travel Control			
	Creep Speed Control Button Allows Low Speed Travel with Handle Vertical for			
	I I			
	Maneuvering in Tight Areas			
	Wrap Around Traction Reversing Switch			
	Wire Mesh Mast Shield			
	Electromagnetic Park Brake with Service Override			
	Electronic Horn			
	· 158 A.H. @ 6 Hr. Rate Power Pack (185 A.H. @ 20 Hr. Rate) with 25 Amp			
	On-Board Charger (110V; 60 Cycle)			
	Battery Connector – 175 Amp, Type X Red, Pos. B-20" Lead Length			
	Low Battery Lift Interrupt Without Display			
	· Operator's Manual			
	Total	\$7,863.00	\$8,334.00	see above
	Wesco Distribution submitted a NO BID.			
	Business classification	Non Specified	Non Specified	SB
	FOB	•		DP
	Estimated delivery	1/17/2008	13 wks ARO	4 wks
	Terms			N10
	5	1.00	approved credit	1110
	Reference number	Non Specified		Non Specified
	Warranty			Copy attached
-+	vvairanty	oo days	4 mths/750 hrs	Copy allacited
			12 mths/powertrain	
-+	Quotation effective until	2/17/2008		2/20/2008
	Quotation enective until	2/11/2000	2/29/2008	2/20/2000
	BID AWARDED TO YALE CAROLINAS, INC AS THE LOWEST RESPONSIBLE BIDDER MEETING	CDECIFICATIONS		